



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
|-----------------|-------------|----------------------|---------------------|------------------|

10/799,671

03/15/2004

Jari Mutikainen

47092.00075

8603

32294

7590

03/10/2009

SQUIRE, SANDERS & DEMPSEY L.L.P.

8000 TOWERS CRESCENT DRIVE

14TH FLOOR

VIENNA, VA 22182-6212

EXAMINER

LIU, BEN H

ART UNIT

PAPER NUMBER

2416

MAIL DATE

DELIVERY MODE

03/10/2009

PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

| | | | |
|------------------------------|--------------------------------------|--|--|
| Office Action Summary | Application No. 10/799,671 | Applicant(s) MUTIKAINEN ET AL. | |
| | Examiner BEN H. LIU | Art Unit 2416 | |

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 01 December 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-12, 14-35, 37-43 and 45-59 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-12, 14-35, 37-43 and 45-59 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Response to Amendment

1. This is in response to an amendment/response filed on December 1st, 2008.
2. Claims 2, 4, 9, 32-34, 54, and 57-58 have been amended.
3. No claims have been cancelled.
4. No new claims have been added.
5. Claims 1-12, 14-35, 37-43, and 45-59 are currently pending.

Claim Rejections - 35 USC § 103

6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

7. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

Art Unit: 2416

8. This application currently names joint inventors. In considering patentability of the claims under 35 U.S.C. 103(a), the examiner presumes that the subject matter of the various claims was commonly owned at the time any inventions covered therein were made absent any evidence to the contrary. Applicant is advised of the obligation under 37 CFR 1.56 to point out the inventor and invention dates of each claim that was not commonly owned at the time a later invention was made in order for the examiner to consider the applicability of 35 U.S.C. 103(c) and potential 35 U.S.C. 102(e), (f) or (g) prior art under 35 U.S.C. 103(a).

9. Claims 1-10, 14-35, 37-43, and 45-59 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hyllander et al. (U.S. Patent 7,065,199) in view of Chaney et al. (U.S. Patent 7,184,415).

For claim 1, Hyllander et al. disclose a method comprising:

receiving a temporary routing number at a user terminal (*see column 3 lines 1-7, which recite a subscriber that receives a server's telephone number as a temporary routing number*);

establishing a circuit-switched call leg connection from the user terminal (*see figure 2, which recite a user terminal 8 that establishes a circuit-switched call leg to GSM network 9*) to a packet-switched network (*see figure 2, which recite extending the circuit-switched connection from user terminal 8 to packet-switched Internet 3*) via a circuit-switched network using the routing number, wherein the connection is used for providing a packet-switched call service to the circuit-switched network (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*);

Art Unit: 2416

transmitting, via a data path, a call request directed to an application server which provides the call service (*see column 2 lines 57-63, which recite transmitting a connection request to a telephony/Internet application server that provides a call service*);

receiving, via the data path, the temporary routing number as a call routing number for a requested call in response to the call request (*see column 3 lines 1-7, which recite the subscriber that receives a server's telephone number as a temporary routing number*); and

using the received call routing number to set up the circuit-switched call leg as a call leg of the call (*see column 3 lines 8-14 and figure 2, which recite the subscriber terminal 8 that establishes a circuit-switched call leg to the GSM network 9 by calling the provided server telephone number*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a

Art Unit: 2416

telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 2, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the receiving comprises receiving a routing number comprising an E.164 number (*see column 2 lines 57-63, which recite delivering the server telephone number as the routing number*).

For claim 3, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the delivering step comprises performing using at least one session initiation protocol session setup message. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the

Art Unit: 2416

functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 4, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the session initiation protocol session is kept active during the circuit-switched call. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*) for the duration of the call (*see column 12 lines 19-23*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 5, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, further comprising detecting whether the circuit-switched call leg is supported by the user terminal and the packet-switched network before the delivering step (*see column 3 lines 61-62, which recite determining whether a call connection is possible*).

Art Unit: 2416

For claim 6, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the detecting comprises performing within a registration procedure (*see column 3 lines 52-62, which recite determining whether a call connection is possible when a call request is registered*).

For claim 7, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, wherein the establishing comprises establishing the circuit-switched call leg comprising a call leg from an originating call (*see column 3 lines 8-14, which recite receiving a circuit switched call from the originating caller*).

For claim 8, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the establishing step comprises establishing the circuit-switched call leg comprising a call leg from a terminating call (*see figure 1, which recite establishing a connection to a terminating telephone 2 on a circuit switched PSTN network*).

For claim 9, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, wherein the receiving step comprises delivering the routing number to the user terminal from a call control element of the packet-switched network (*see column 3 lines 1-7, which recite delivering a routing number from a telephony/internet server*).

For claim 10, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the establishing comprises locating the user terminal outside a home network of the user terminal. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that facilitates

Art Unit: 2416

communication between terminals that are outside of their home networks (*see figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to facilitate communication between terminals outside of their home networks as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. Communication between terminals outside of their home networks can be implemented by installing a Presence and Instant Messaging (PIM) server 18 as taught by Chaney et al. in the IP network to forward messages to mobile terminals outside of their home networks. The motivation for facilitating communication between terminals outside of their home network with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing the network to provide services to a terminal by only knowing its network ID.

For claim 14, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, further comprising the step of selecting participants of the call and adding to the call request an information specifying the selected participants (*see column 2 lines 57-63, which recite a connection request specifying the participants*).

For claim 15, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the transmitting comprises performing based on a pre-configured address information (*see column 8 lines 32-34, which recite transmitting the specific address of the subscriber and Internet user*).

Art Unit: 2416

For claim 16, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, further comprising setting the pre-configured address information in a service subscription stage (*see column 8 lines 27-34, which recite transmitting the specific address of the subscriber and Internet user while requesting for a connection*).

For claim 17, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, further comprising adding session-related information to the call request, the session-related information comprising at least one of a subject: picture of the subject, payer of the call, importance of the call session, animation, video clip, sound clip, and textual description (*see column 2 lines 57-63, which recite transmitting a connection request with a textual description*).

For claim 18, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the transmitting comprises transmitting via the data path comprising a short message service channel (*see column 2 lines 27-30, which recite using a SMS channel*).

For claim 19, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the transmitting step comprises transmitting via the data path that comprises a unstructured supplementary service data, wireless application protocol, or hyper text transfer protocol channel (*see column 10 lines 43-55, which recite transmitting along a data path using GSM alternate speech/data services*).

For claim 20, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the transmitting and receiving steps comprise using session initiation

Art Unit: 2416

protocol. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 21, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the transmitting and receiving steps comprise performing using at least one session initiation protocol or service description protocol extension for communicating circuit-switched specific information. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as

Art Unit: 2416

taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 22, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the providing step comprises setting up the circuit-switched connection to a media gateway control device which then routes the circuit-switched call to the application server *(see column 8 lines 10-20, which recite a server that receives a circuit switched call from a subscriber and transfers that call to an Internet user)*.

For claim 23, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network, further comprising converting the routing number into a packet-switched call address at the media gateway control device *(see column 8 lines 10-20, which recite associating a telephone number with an Internet address to allow for a connection between the two networks)*.

For claim 24, Hyllander et al. disclose all the subject matter of the claimed invention further comprising: reserving the routing number as a temporary conference routing number at the application server during establishment of the conference call; and releasing the routing number for reuse after releasing the conference call. However, Hyllander et al. disclose a system for establishing a connection between a circuit-switched network and packet-switched network

Art Unit: 2416

that provides a telephone number for subscribers to access conference calls hosted by the server (*see column 2 lines 57-63*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to designate telephone numbers to serve specific conference calls. Specific telephone numbers can be used with the server that hosts conference calls by configuring the server to accept and manage a calls made to a pool of telephone numbers allocated to the server. The motivation for using a specific telephone numbers is to increase the capacity of the server by allowing the reuse of telephone numbers.

For claim 25, Hyllander et al. disclose all the subject matter of the claimed invention with the exception that the method for establishing a connection between a circuit-switched network and packet-switched network further comprises forwarding a join request to join the conference call from the application server to other participants specified in the conference request via a data path. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request is transmitted using a SIP INVITE message (*see column 5 lines 22-31*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a

Art Unit: 2416

connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 26, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the forwarding comprises transmitting the request using a session initiation protocol invite message triggered by a received session initiation protocol refer message. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request is transmitted using a SIP INVITE message (*see column 5 lines 22-31*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 27, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the forwarding comprises forwarding the join request, the join

Art Unit: 2416

request comprising: at least one of an identification of the conference initiator; a subject of the conference call; a price of the conference call leg; and an information about a moderation of the conference call, an animation, a video clip, a sound clip, and a textual description. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request is transmitted using a SIP REFER message that includes a textual description (*see column 8 lines 55-64*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 28, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises forwarding, via another data path, the conference routing number from the application server to a requested participant specified in the conference request to indicate that the conference call will be established from the conference

Art Unit: 2416

number to the requested participant, wherein at least one circuit-switched connection is set up from the application server using the conference number as a calling party number via a media gateway control device, which then routes the conference call to the requested participant.

Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request is transmitted using a SIP INVITE message to another participant (*see column 5 lines 22-31*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 29, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises forwarding a kick-out request to the application server via the data path to have a participant excluded from the conference call.

Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a

Art Unit: 2416

telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The SIP standard provides a BYE message that allows established connections to be terminated thus excluding the user of the terminated connection from the conference. Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 30, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises forwarding the kick-out request, said kick-out request comprises an identification of the conference call and an identification of at least one the participant to be excluded. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The SIP standard provides a BYE message that allows established connections to be terminated thus excluding the user of the terminated connection from the conference. Thus, it would have been

Art Unit: 2416

obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 31, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the receiving comprises receiving the temporary routing number for the call, the call supports at least one of: an audio component, a non-real time video component; an application component; and a messaging component (*see column 2 lines 43-56, which recite establishing a telephony/Internet connection*).

For claim 32, Hyllander et al. disclose a method for establishing a connection between a circuit-switched network and packet-switched network wherein the connection set-up comprises a call policy control protocol over an Mt interface as a data path (*see column 3 lines 52-62, which recite a server that implements call policies by storing and assigning an address list, server telephone number, and information that the call connection is possible*).

For claim 33, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises the steps of forwarding, via another data path, a join request to join the conference call from a requesting participant to at least one requested participant specified in the conference request, wherein the join request comprises the conference routing number and a connection setup step comprises setting up a circuit switched connection from the at least one requested participant to application server using the conference routing number. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request is forwarded to all the participants (*see column 9 lines 11-14*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

Art Unit: 2416

For claim 34, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises forwarding the request using a session initiation protocol Refer message and the connection setup step comprises establishing the at least one circuit switched connection using session initiation protocol Invite message. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The join request comprises SIP REFER messages that are forwarded to all the participants (*see column 9 lines 11-14*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 35, Hyllander et al. disclose an apparatus comprising:

Art Unit: 2416

a communicator configured to receive a temporary routing number delivered to a user terminal (*see column 3 lines 1-7, which recite a subscriber that receives a server's telephone number as a temporary routing number*);

an establisher configured to establish circuit-switched call leg connection from the user terminal (*see figure 2, which recite a user terminal 8 that establishes a circuit-switched call leg to GSM network 9*) to a packet-switched network (*see figure 2, which recite extending the circuit switched-connection from user terminal 8 to packet-switched Internet 3*) via a circuit-switched network using the temporary routing number, wherein the connection is used for providing a packet-switched call service to the circuit-switched network (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*);

a transceiver configured to transmit, via a data path, a call request directed to an application server which provides the call service (*see column 2 lines 57-63, which recite transmitting a connection request to a telephony/Internet application server that provides a call service*);

the transceiver also configured to receive, via the data path, the temporal, routing number as a call routing number for a requested call in response to the call request (*see column 3 lines 1-7, which recite the subscriber that receives a server's telephone number as a temporary routing number*); and

a processor configured to use the received call routing number to set up the circuit-switched call leg as a call leg of the call (*see column 3 lines 8-14, which recite the subscriber that establishes a circuit-switched call leg by calling the provided server telephone number*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 37, Hyllander et al. disclose a terminal device for establishing a connection between a circuit-switched network and packet-switched network wherein the communication means is configured to use a short message service channel for forwarding the call request (*see column 2 lines 27-30, which recite using a SMS channel*).

Art Unit: 2416

For claim 38, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the communication means is configured to use a session initiation protocol message for forwarding the conference request. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 39, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the communication means is configured to use at least one session initiation protocol or service description protocol extension for communicating circuit-switched specific information. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control

Art Unit: 2416

signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 40, Hyllander et al. disclose a terminal device for establishing a connection between a circuit-switched network and packet-switched network wherein the communication means and the establishing means are integrated in a telephony application of the terminal device *(see column 2 lines 4-11, which recite a SMS communication means used to establish a connection that is integrated in the mobile terminals)*.

For claim 41, Hyllander et al. disclose a terminal device for establishing a connection between a circuit-switched network and packet-switched network wherein a call application is implemented as a native client application or as a midlet application *(see column 2 lines 4-11, which recite a SMS communication means used to establish a call that is integrated in the mobile terminals)*.

For claim 42, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the the communicator is configured to transmit the conference request in consequence of receiving a first request from another user. Chaney et al. from the

Art Unit: 2416

same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The terminal transmits a conference request SIP REFER message 103 in response to a first conference request SIP REFER message 102 (*see figure 5*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 43, Hyllander et al. disclose an apparatus comprising:

a communicator configured to receive from a circuit-switched network, a connection request via a data path (*see column 2 lines 57-63 and figure 2, which recite receiving a connection request at a telephony/Internet server 11*); and

a deliverer configured to deliver a temporary routing number to a terminal device for the circuit-switched network via the data path (*see column 3 lines 1-7 and figure 2, which recite a telephone/Internet server 11 that transmits the server's telephone number as a temporary routing number*), wherein a connection from a packet switched network to a circuit-switched network

Art Unit: 2416

(see figure 2, which recite a connection from the mobile terminal 8 to the circuit-switched GSM network 9) is used to provide a packet-switched call service to the circuit-switched network, the connection request comprising a call request, and the temporal, routing number comprising a call routing number (see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network *(see abstract)* that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 *(see figure 3b and figure 8)*. Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. *(see column 2 lines 28-32)* with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

Art Unit: 2416

For claim 45, Hyllander et al. disclose an apparatus for establishing a connection between a circuit-switched network and packet-switched network, further comprising allocating means for allocating said call routing number as a temporary E.164 number to said call (*see column 2 lines 57-63, which recite using the server telephone number as the routing number*).

For claim 46, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein said allocator is configured to reserve a plurality of E.164 numbers for a plurality of conference calls. However, Hyllander et al. disclose a system for establishing a connection between a circuit-switched network and packet-switched network that provides a telephone number for subscribers to access conference calls hosted by the server (*see column 2 lines 57-63*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use a plurality of telephone numbers to host a plurality of conference calls. A plurality of telephone numbers can be used with the server that hosts conference calls by configuring the server to accept calls made to a plurality of telephone numbers. The motivation for using a plurality of telephone numbers is to increase the functionality of the server to handle a plurality of conference calls.

For claim 47, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein said reserved plurality of E.164 numbers comprises a plurality of toll-free numbers and a plurality of charged numbers. However, Hyllander et al. disclose a system for establishing a connection between a circuit-switched network and packet-switched network that provides a telephone number for subscribers to access conference calls hosted by the server (*see column 2 lines 57-63*). The telephone numbers can be either toll-free numbers or charged numbers. Thus, it would have been obvious to the person of ordinary skill in the art at

Art Unit: 2416

the time of the invention to use a plurality of toll-free and charged telephone numbers to host a plurality of conference calls. A plurality of toll-free and charged telephone numbers can be used with the server that hosts conference calls by configuring the server to accept calls made to a plurality of telephone numbers. The motivation for using a plurality of toll-free and charged telephone numbers is to increase the functionality of the server to handle a plurality of conference calls.

For claim 48, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein said allocator is configured to select said E.164 number from said plurality of charged numbers included in said conference request. However, Hyllander et al. disclose a system for establishing a connection between a circuit-switched network and packet-switched network that provide a telephone number for subscribers to access conference calls hosted by the server (*see column 2 lines 57-63*). The telephone numbers can be either toll-free numbers or charged numbers. Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to select a number from a plurality of charged telephone numbers to host a plurality of conference calls. A plurality of charged telephone numbers can be used with the server that hosts conference calls by configuring the server to accept calls made to a plurality of telephone numbers. The motivation for using a plurality of charged telephone numbers is to increase the functionality of the server to handle a plurality of conference calls.

For claim 49, Hyllander et al. disclose an apparatus for establishing a connection between a circuit-switched network and packet-switched network wherein said communication means is configured to send a call routing number via a respective data path to other participants

Art Unit: 2416

specified in a call request (*see column 3 lines 1-7, which recite sending a server's telephone number as a temporary routing number*).

For claim 50, Hyllander et al. disclose an apparatus for establishing a connection between a circuit-switched network and packet-switched network, further comprising: checker configured to control whether callers of received calls relating to said call match with said other participants specified in said call request (*see column 8 lines 44-50, which recite identifying the calling party and associating the telephone call with a previously determined Internet address requested by the calling party*).

For claim 51, Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the method for establishing a connection between a circuit-switched network and packet-switched network further comprises a connection controller configured to control individual call legs of participants in a media gateway device. Chaney et al. from the same or similar fields of endeavor disclose a subscriber service in a telecommunications network (*see abstract*) that utilizes SIP control signaling for call setup and call control (*see column 2 lines 36-45*). The SIP standard provides a INVITE, REFER, and BYE message that allows individual call legs to be manage. Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use SIP control signaling for call setup and call control as taught by Chaney et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. SIP control signaling for call setup and call control can be implemented by installing a modified conference server 152 as taught by Chaney et al. in the IP network to send and receive SIP messages with a SIP enabled mobile terminal. The motivation for using SIP control signaling for call setup and call control

Art Unit: 2416

with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the functionality of the network by allowing terminals to request various services on a network without knowing the network ID of the corresponding servers.

For claim 52, Hyllander et al. disclose an apparatus for establishing a connection between a circuit-switched network and packet-switched network, further comprising an interface configured to provide a direct connection to a media gateway control device to enable routing of a set-up call for a call from said circuit-switched network to an application server (*see column 8 lines 44-51, which recite a server that forwards a call from a calling party to an Internet address*).

For claim 53, Hyllander et al. disclose an apparatus for establishing a connection between a circuit-switched network and packet-switched network, further comprising an implementer configured to implement media gateway controller functions in the said server device (*see column 8 lines 44-51, which recite a server that performs the functions of a gateway controller to setup and maintain connections between a circuit switched network and packet switched network*).

For claim 54, Hyllander et al. disclose a computer program embodied on a computer-readable medium, the computer program configured to control a processor to perform operations comprising:

receiving a temporary routing number at a user terminal (*see column 3 lines 1-7, which recite a subscriber that receives a server's telephone number as a temporary routing number*);

establishing a circuit-switched call leg connection from a user terminal (*see figure 2, which recite a user terminal 8 that establishes a circuit-switched call leg to GSM network 9*) to a

Art Unit: 2416

packet-switched network (*see figure 2, which recite extending the circuit-switched connection from user terminal 8 to packet-switched Internet 3*) via a circuit-switched network using the routing number, wherein the connection is used for providing a packet-switched call service to the circuit-switched network (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*);

transmitting, via a data path, a call request directed to an application server which provides the call service (*see column 2 lines 57-63, which recite transmitting a connection request to a telephony/Internet application server that provides a call service*);

receiving, via the data path, the temporary routing number as a call routing number for a requested call in response to the call request (*see column 3 lines 1-7, which recite the subscriber that receives a server's telephone number as a temporary routing number*); and

using the received call routing number to set up the circuit-switched call leg as a call leg of the call (*see column 3 lines 8-14 and figure 2, which recite the subscriber terminal 8 that establishes a circuit-switched call leg to the GSM network 9 by calling the provided server telephone number*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more

Art Unit: 2416

participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 55, Hyllander et al. disclose a computer program embodied on a computer-readable medium, the computer program, the computer program configured to control a processor to perform operations comprising:

receiving, from a circuit-switched network, a connection request via a data path (*see column 2 lines 57-63 and figure 2, which recite receiving a connection request at a telephony/Internet server 11*); and

deliver a temporary routing number to a terminal device for the circuit-switched network via the data path (*see column 3 lines 1-7 and figure 2, which recite a telephone/Internet server 11 that transmits the server's telephone number as a temporary routing number*), wherein a connection from a packet switched network to a circuit-switched network (*see figure 2, which recite a connection from the mobile terminal 8 to the circuit-switched GSM network 9*) is used to provide a packet-switched call service to the circuit-switched network, the connection request

Art Unit: 2416

comprising a conference request, and the temporary routing number comprising a call routing number (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 56, Hyllander et al. disclose an apparatus comprising:

Art Unit: 2416

communication means for receiving a temporary routing number delivered to a user terminal (*see column 3 lines 1-7, which recite a subscriber that receives a server's telephone number as a temporary routing number*);

establishing means for establishing a circuit-switched call leg connection from the user terminal (*see figure 2, which recite a user terminal 8 that establishes a circuit-switched call leg to GSM network 9*) to a packet-switched network (*see figure 2, which recite extending the circuit-switched connection from user terminal 8 to packet-switched Internet 3*) via a circuit-switched network using the temporary routing number, wherein the connection is used for providing a packet-switched call service to the circuit-switched network (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*);

transmission means for transmitting, via a data path, a call request directed to an application server which provides the call service (*see column 2 lines 57-63, which recite transmitting a connection request to a telephony/Internet application server that provides a call service*);

receiving means for receiving, via the data path, the temporary routing number as a call routing number for a requested call in response to the call request (*see column 3 lines 1-7, which recite the subscriber that receives a server's telephone number as a temporary routing number*); and

processing means for using the received call routing number to set up the circuit-switched call leg as a call leg of the call (*see column 3 lines 8-14 and figure 2, which recite the subscriber*

Art Unit: 2416

terminal 8 that establishes a circuit-switched call leg to the GSM network 9 by calling the provided server telephone number).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 57, Hyllander et al. disclose an apparatus comprising:

Art Unit: 2416

communication means for receiving, from a circuit-switched network, a connection request via a data path (*see column 2 lines 57-63 and figure 2, which recite receiving a connection request at a telephony/Internet server 11*); and

delivering means for delivering a temporary routing number to a terminal device for the circuit-switched network via the data path (*see column 3 lines 1-7 and figure 2, which recite a telephone/Internet server 11 that transmits the server's telephone number as a temporary routing number*), wherein a connection from a packet switched network to a circuit-switched network (*see figure 2, which recite a connection from the mobile terminal 8 to the circuit-switched GSM network 9*) is used to provide a packet-switched call service to the circuit-switched network, the connection request comprising a call request, and the temporary routing number comprising a call routing number (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152

Art Unit: 2416

as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

For claim 58, Hyllander et al. disclose a method comprising:

receiving, from a circuit-switched network, a connection request via a data path (*see column 2 lines 57-63 and figure 2, which recite receiving a connection request at a telephony/Internet server 11*); and

delivering a temporary routing number to a terminal device for the circuit-switched network via the data path (*see column 3 lines 1-7 and figure 2, which recite a telephone/Internet server 11 that transmits the server's telephone number as a temporary routing number*), wherein a connection from a packet switched network to a circuit-switched network (*see figure 2, which recite a connection from the mobile terminal 8 to the circuit-switched GSM network 9*) is used to provide a packet-switched call service to the circuit-switched network, the connection request comprising a call request, and the temporary routing number comprising a call routing number (*see figure 2, which recite a telephony/Internet server 11 that provides a packet-switched call service to the GSM circuit-switched network 9*).

Hyllander et al. disclose all the subject matter of the claimed invention with the exception wherein the call service is a conference call service. Chaney et al. from the same or similar

Art Unit: 2416

fields of endeavor disclose a conference system and method in a telecommunications network (*see abstract*) that includes a conference server 152 that receives a conference request at step 82 and invites participants to join the conference call at step 84 (*see figure 3b and figure 8*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to use the modified conference server 152 as taught by Chaney et al. to invite two or more participants to a conference call with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. The conference service system and method can be implemented by installing the modified conference server 152 as taught by Chaney et al. with the network of the conference service and method as taught by Hyllander et al. The motivation for using the conference system and method in a telecommunications network including a modified conference server that provides a conference service to multiple participants as suggested by Chaney et al. (*see column 2 lines 28-32*) with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the accessibility of the system by providing access to the conference service when the user does not know the network ID of the server that provides such services.

10. Claims 11-12 are rejected under 35 U.S.C. 103(a) as being unpatentable over Hyllander et al. (U.S. Patent 7,065,199) and of Chaney et al. (U.S. Patent 7,184,415) as applied to claims 1 and further in view of Hirni et al. (U.S. Patent 6,731,609).

For claim 11, Hyllander et al. and Chaney et al. disclose all the subject matter of the claimed invention with the exception that the method for establishing a connection between a circuit-switched network and packet-switched network further comprises the step of converting

Art Unit: 2416

the circuit-switched call leg into a voice-over internet protocol connection in a core network of the packet-switched network. Hirni et al. from the same or similar fields of endeavor disclose a telephony system for conducting multimedia telephonic conferences between a packet-based network and circuit switched PSTN network (*see abstract*) that provides calls using VOIP (*see column 3 lines 52-67*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to deploy a telephony system using VOIP as taught by Hirni et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. and Chaney et al. A telephony system using VOIP can be implemented by installing agent systems 18 to handle multimedia telephone calls as taught by Hirni et al. with the in the IP network. The motivation for using a VOIP voice telephony system with the method for establishing a connection between a circuit-switched network and packet-switched network is to reduce the cost of the system for users.

For claim 12, Hyllander et al. and Chaney et al. disclose all the subject matter of the claimed invention with the exception wherein the establishing step comprises performing using integrated services digital network user part. Hirni et al. from the same or similar fields of endeavor disclose a telephony system for conducting multimedia telephonic conferences between a packet-based network and circuit switched PSTN network (*see abstract*) that provides calls using ISDN (*see column 14 lines 35-46*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to deploy a telephony system using ISDN as taught by Hirni et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. and Chaney et al. A telephony system using ISDN can be implemented by providing a Q.931 module to handle the

Art Unit: 2416

ISDN connection control protocol as by Hirni et al. in the server system. The motivation for using a ISDN telephony system with the method for establishing a connection between a circuit-switched network and packet-switched network is to improve the compatibility of the network with various subscriber access means.

11. Claim 59 is rejected under 35 U.S.C. 103(a) as being unpatentable over Hyllander et al. (U.S. Patent 7,065,199) and of Chaney et al. (U.S. Patent 7,184,415) as applied to claims 1 and further in view of Kaczmarczyk et al. (U.S. Patent 6,775,269).

For claim 59, Hyllander et al. and Chaney et al. disclose all the subject matter of the claimed invention with the exception that the method for establishing a connection between a circuit-switched network and packet-switched network further comprises controlling individual call legs of participants in a media gateway device. Kaczmarczyk et al. from the same or similar fields of endeavor disclose a method and system for routing telephone calls between a circuit switched PSTN network 12 and packet switched network 14 through a Media Gateway 18 (*see abstract and figure 1*). Thus, it would have been obvious to the person of ordinary skill in the art at the time of the invention to deploy the media gateway 18 to establish calls between a circuit switched PSTN network 12 and packet switched network 14 as taught by Kaczmarczyk et al. with the method for establishing a connection between a circuit-switched network and packet-switched network as taught by Hyllander et al. and Chaney et al. The media gateway 18 as taught by Kaczmarczyk et al. can be implemented by using the media gateway 18 in place of the telephony/Internet server 11 as taught by Hyllander et al. The motivation for using media gateway 18 as suggested by Kaczmarczyk et al. with the method for establishing a connection

Art Unit: 2416

between a circuit-switched network and packet-switched network is to improve the routing of telephone calls (*see column 2 lines 26-30*).

Response to Arguments

12. Claims 2 and 9 were previously rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. It is noted with appreciation that the Applicant has amended the claims to overcome the rejection. In response, the 35 U.S.C. 112, second paragraph rejection has been withdrawn.

13. It is noted with appreciation that the Applicant has carefully considered the previous Office Action and the cited prior art references. However, the Applicant's arguments filed December 1st, 2008 regarding the 35 USC 103(a) rejections have been fully considered but are not persuasive.

The Applicant argues in page 22 of the remarks that the "a combination of Hyllander and Chaney fails to disclose or suggest all the limitations of the rejected claims. For example, a combination of Hyllander and Chaney fails to disclose or suggest 'receiving a temporary routing number at a user terminal; establishing a circuit-switched call leg connection from said user terminal to a packet-switched network via a circuit-switched network using said routing number, wherein said connection is used for providing a packet-switched conference call service to said circuit-switched network...and using said received conference routing number to set up said

Art Unit: 2416

circuit-switched call leg as a call leg of said conference call,' as recited in claim 1, and as similarly recited in claims 35, 43, and 54-58."

In support of this argument, the Applicant asserts in page 23 of the remarks that "Hyllander relates to a totally different problem and does not suggest delivering the temporary routing number in a packet-switched session establishment and using the circuit-switched call leg as a bearer for the established session." In response to applicant's argument that "Hyllander relates to a totally different problem," a recitation of the intended use of the claimed invention must result in a structural difference between the claimed invention and the prior art in order to patentably distinguish the claimed invention from the prior art. If the prior art structure is capable of performing the intended use, then it meets the claim.

In response to applicant's argument that the references fail to show certain features of applicant's invention, it is noted that the features upon which applicant relies (i.e. "delivering the temporary routing number in a packet-switched session establishment") are not recited in the rejected claim(s). Although the claims are interpreted in light of the specification, limitations from the specification are not read into the claims. See *In re Van Geuns*, 988 F.2d 1181, 26 USPQ2d 1057 (Fed. Cir. 1993). It is noted that Hyllander discloses receiving, via the data path, the temporary routing number as a call routing number for a requested call in response to the call request as recited in claim 1 (*see column 3 lines 1-7, which recite the subscriber that receives a server's telephone number as a temporary routing number*). Hyllander further discloses using the received call routing number to set up the circuit-switched call leg as a call leg of the call as recited in claim 1 (*see column 3 lines 8-14 and figure 2, which recite the subscriber terminal 8*

Art Unit: 2416

that establishes a circuit-switched call leg to the GSM network 9 by calling the provided server telephone number).

The Applicant further argues in page 23 of the remarks that “similarly, Chaney fails to disclose the features mentioned above.” In response to applicant's arguments against the references individually, one cannot show nonobviousness by attacking references individually where the rejections are based on combinations of references. See *In re Keller*, 642 F.2d 413, 208 USPQ 871 (CCPA 1981); *In re Merck & Co.*, 800 F.2d 1091, 231 USPQ 375 (Fed. Cir. 1986).

For at least the reasons provided above, the Applicant's arguments regarding the independent claim are not persuasive. The Applicant further argues that since the dependent claims depend on the argued independent claims, they are patentable at least by virtue of their dependencies. Since the Applicant's arguments regarding the independent claims are not persuasive, the applicant's arguments regarding the dependent claims are also not persuasive.

Conclusion

14. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37

Art Unit: 2416

CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to BEN H. LIU whose telephone number is (571)270-3118. The examiner can normally be reached on 9:00AM to 6:30PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ricky Ngo can be reached on (571)272-3139. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Ricky Ngo/
Supervisory Patent Examiner, Art Unit 2416

BL